



Item # _____ Job # _____

Provides high visibility and easy 4-way access. Ensures quick and efficient inventory control. Ideal for mobile storage requirements. Allows air to circulate throughout, eliminating dust and dirt build-up. Allows you to keep linens, food items, stocked products and other regularly used items on hand, throughout the workplace.

TRUCK: Consists of 4 posts, 4 wire shelves, plastic shelf clips, donut bumpers and 5" dia. swivel casters. Posts are 63"H. Overall truck height is 69". Casters are available in resilient rubber wheel stem casters that have an 800 lb. load capacity or polyurethane wheel stem casters that have a 1200 lb. load capacity or 8" full pneumatic stem casters with a 1200 lb. capacity.

SHELVES: Constructed of open wire design offering greater light penetration and visibility, lighter weight, air circulation and minimal dust and dirt accumulation.

POSTS: 1 in. O.D. round tubing, 16 gauge (0.062 in.) thickness. Rolled grooves spaced at 1 in. on centers along their length. The top of the post have a finished plastic cap and the post bottom have a die cast insert with adjustable leveling foot. At each rolled groove there are consecutive numbers starting at the bottom of the post to facilitate installation of clips.

METHOD OF ASSEMBLY: Frustal-Conical design incorporating a two part tapered plastic sleeve. Engagement and locking are accomplished with a protruding bead on the inner circumference of the plastic sleeve which will match the groove on the post. Two plastic sleeves attach to each corner post for each shelf. Both the sleeves and the corner fitting of the shelves have the identical taper to create a wedge effect, thereby locking the shelf securely in a rigid position. No screws or other fittings are required for assembly. Shelves vertically adjust on 1 in. increments.

FINISHES: Shelves and Posts are available in four finishes:

(A) POLY-Z-BRITE: Clear epoxy power coat electrostatically applied over brite zinc-chromate electro plating. Protected by Nexgard, an anti microbial agent that protects the epoxy coating from bacteria, mold and mildew that causes stains, odors and degradation.

(B) CHROME: Brite, high gloss chrome over nickel electro plating.

(C) NEXELON: Blue metallic epoxy powder coat electrostatically applied over zinc-chromate electro plating and chemical conversion under coat. Protected by Nexgard, an anti microbial agent that protects the epoxy coating from bacteria, mold and mildew that causes stains, odors and degradation.

(D) STAINLESS STEEL: Type 304 electropolished high gloss finish.



WIRE SHELF STEM CASTER TRUCKS

STEM CASTER



POLYURETHANE SWIVEL

1 1/4" x 5"
300 Lb. Capacity



PNEUMATIC SWIVEL

2 1/2" x 8"
300 Lb. Capacity



RUBBER SWIVEL

1 1/4" x 5"
200 Lb. Capacity

Note: Load capacity ratings are per caster. All Stem casters include donut bumpers.



NEXEL INDUSTRIES INC.
11 Harbor Park Drive
Port Washington, NY 11050
U.S.A

1-800-245-6682

NY: 1-516-484-5225

FAX: 1-516-625-0084

E-mail: nexelinfo@nexelwire.com

www.nexelwire.com



WIRE SHELF STEM CASTER TRUCKS



WIRE SHELF STEM CASTER TRUCKS

Item # _____ Job # _____

POLYFLORITE				
Size W" x L"	Rubber Wheel Casters Model No.	Polyurethane Wheel Casters Model No.	Pneumatic Wheel Casters Model No.	Weight Lbs.
18 x 36	C1836RZ	C1836PZ	C1836NZ	62
18 x 48	C1848RZ	C1848PZ	C1848NZ	72
18 x 60	C1860RZ	C1860PZ	C1860NZ	92
21 x 36	C2136RZ	C2136PZ	C2136NZ	68
21 x 48	C2148RZ	C2148PZ	C2148NZ	80
21 x 60	C2160RZ	C2160PZ	C2160NZ	96
24 x 36	C2436RZ	C2436PZ	C2436NZ	76
24 x 48	C2448RZ	C2448PZ	C2448NZ	88
24 x 60	C2460RZ	C2460PZ	C2460NZ	108



CHROME				
Size W" x L"	Rubber Wheel Casters Model No.	Polyurethane Wheel Casters Model No.	Pneumatic Wheel Casters Model No.	Weight Lbs.
18 x 36	C1836RC	C1836PC	C1836NC	62
18 x 48	C1848RC	C1848PC	C1848NC	72
18 x 60	C1860RC	C1860PC	C1860NC	92
21 x 36	C2136RC	C2136PC	C2136NC	68
21 x 48	C2148RC	C2148PC	C2148NC	80
21 x 60	C2160RC	C2160PC	C2160NC	96
24 x 36	C2436RC	C2436PC	C2436NC	76
24 x 48	C2448RC	C2448PC	C2448NC	88
24 x 60	C2460RC	C2460PC	C2460NC	108


SHELF DIVIDERS

Size"	Model No.
14	AD814C
18	AD818C
21	AD821C
24	AD824C

LEDGES

Size"	Model No.
14	AL414C
18	AL418C
21	AL421C
24	AL424C
30	AL430C
36	AL436C
42	AL442C
48	AL448C
54	AL454C
60	AL460C
72	AL472C

NEXELON				
Size W" x L"	Rubber Wheel Casters Model No.	Polyurethane Wheel Casters Model No.	Pneumatic Wheel Casters Model No.	Weight Lbs.
18 x 36	C1836RN	C1836PN	C1836NN	62
18 x 48	C1848RN	C1848PN	C1848NN	72
18 x 60	C1860RN	C1860PN	C1860NN	92
21 x 36	C2136RN	C2136PN	C2136NN	68
21 x 48	C2148RN	C2148PN	C2148NN	80
21 x 60	C2160RN	C2160PN	C2160NN	96
24 x 36	C2436RN	C2436PN	C2436NN	76
24 x 48	C2448RN	C2448PN	C2448NN	88
24 x 60	C2460RN	C2460PN	C2460NN	108



STAINLESS STEEL				
Size W" x L"	Rubber Wheel Casters Model No.	Polyurethane Wheel Casters Model No.	Pneumatic Wheel Casters Model No.	Weight Lbs.
18 x 36	C1836RS	C1836PS	C1836NS	62
18 x 48	C1848RS	C1848PS	C1848NS	72
24 x 36	C2436RS	C2436PS	C2436NS	76
24 x 48	C2448RS	C2448PS	C2448NS	88

NOTE: Locking post collars are recommended for rough use over the road vibration and jolting. Order one per shelf. Part No. APL.

NOTE: If rigid or brake style casters are required for your application, order a starter shelving unit and casters separately. To order shelving units, see spec sheet 100 or Nexel Catalog.

OPTIONAL CASTER SETS

Description: Resilient Rubber Wheel, 1 1/4" x 5", 200 lb. capacity.

Type	Model No.
Swivel (Set of 4)	CA5S4R
Swivel w/Brake (Set of 4)	CA5BR4
Swivel 2 w/Brake (Set of 4)	CA5SBR

Description: Polyurethane Wheel, 1 1/4" x 5", 300 lb. capacity.

Type	Model No.
Swivel (Set of 4)	CA5S4
Swivel w/Brake (Set of 4)	CA5BP4
Swivel, 2 w/Brake (Set of 4)	CA5SB
Swivel, 2 w/Brake, 2 Rigid (Set of 4)	CA5RSB*
Stainless Steel, Swivel, 2 w/Brake (Set of 4)	CA5SBS

Description: Pneumatic Wheel, 2.5" x 8", 300 lb. capacity.

Type	Model No.
2 Swivel, 2 Rigid (Set of 4)	CA85RN*

*Tie Bar required