



NEXELITE PLASTIC MAT SHELVING



Item # _____

Job # _____

Versatile storage system is perfect for storing all your goods, materials and inventory. Sturdy frame comes in our **NEXELON** finish. Polymer composition shelf mats are of a modular design allowing easy removal for cleaning. They have a vented open grid surface that is smooth and crevice-free. Polymer material will never dent, chip, rust, or corrode. Open on all four sides for complete access and superior ventilation. Shelves adjust on 1" increments. A standard shelving unit consists of 4 Nexelite shelves and 4 posts.

1. EASY TO ASSEMBLE: Nexelite assembles in minutes, without tools. Posts have number grooves at 1" increments. Attach the shelf clip to the desired shelf height, and slide shelves over post onto the clips.

2. EASY TO CLEAN: Polymer shelf mats lift off the shelf frame for easy cleaning. Shelf modules are made in three sizes, 12", 15" and 18" that fit into a dishwasher for cleaning.

3. EASY TO MOVE: Nexelite shelving units can become mobile by adding any set of Nexel stem casters.

4. CORROSION RESISTANT AND DURABLE: Nexel polymer shelf mats have a lifetime warranty against rust and corrosion. Posts and shelf frames are coated with our Nexelon finish, which comes with a lifetime warranty against rust and corrosion. Each shelf has up to a 600 lb. capacity.



NEXELITE PLASTIC MAT SHELVING



SHELF MATS CAN BE REMOVED EASILY FOR CLEANING



NEXEL INDUSTRIES INC.
11 Harbor Park Drive
Port Washington, NY 11050
U.S.A

1-800-245-6682

NY: 1-516-484-5225

FAX: 1-516-625-0084

E-mail: nexelinfo@nexelwire.com
www.nexelwire.com



Item # _____ Job # _____

SHELF FRAME AND POSTS:

Blue metallic epoxy powder coat electrostatically applied over zinc chromate electro plating and chemical conversion undercoat. Lifetime warranty against rust and corrosion in wet or dry applications. Protected with NexGard, an anti-microbial agent that protects the epoxy coating from bacteria, mold and mildew, that causes stains, odors and product degradation.

SHELF MATS:

Polymer composition, vented open grid surface.

SHELF CLIPS:

2 part tapered plastic sleeve.

TEMPERATURE RANGE:

-20°F(-29°C) to 125°F(52C) continuous use, with intermittent exposure to 200F(93C)

NEXELITE SHELVES

(complete with frame, mat and shelf clips)

Model	Shelf Size (in.)	W x L (mm.)	Weight (Lbs.)	Weight. (Kg.)
PM1830N	18 x 30	457 x 760	5	2.3
PM1836N	18 x 36	457 x 914	6	2.7
PM1842N	18 x 42	457 x 1066	7	3.2
PM1848N	18 x 48	457 x 1219	8	3.6
PM1854N	18 x 54	457 x 1370	9	4.1
PM1860N	18 x 60	457 x 1524	10	4.5
PM1872N	18 x 72	457 x 1825	12	5.4
PM2430N	24 x 30	610 x 760	7	3.2
PM2436N	24 x 36	610 x 914	8	3.6
PM2442N	24 x 42	610 x 1066	9.5	4.3
PM2448N	24 x 48	610 x 1219	10.5	4.8
PM2454N	24 x 54	610 x 1370	12	5.4
PM2460N	24 x 60	610 x 1524	13	5.9
PM2472N	24 x 72	610 x 1825	16	7.3

POSTS

(with levelers)

Model	Ht. (in.)	Ht. (mm.)	Weight. (Lbs.)	Weight. (Kg.)
P6N	6	152	.5	.23
P14N	14	356	1	.45
P34N	34	864	2	.91
P54N	54	1372	3	1.4
P63N	63	1600	3.5	1.6
P74N	74	1880	4	1.8
P86N	86	2184	5	2.3



Shelves adjust on 1" increments. Numbered posts for quick assembly.



Simply snap together and slide shelf over sleeve for positive locking.

OPTIONAL CASTER SETS

Description: Resilient Rubber Wheel, 1 1/4" x 5", 200 lb. capacity.

Type	Model No.	Weight(Lbs.)	Weight(kg.)
Swivel (Set of 4)	CA5S4R	13	5.9
Swivel w/Brake (Set of 4)	CA5BR4	11	5
Swivel 2 w/Brake (Set of 4)	CA5SBR	10	4.5

Description: Polyurethane Wheel, 1 1/4" x 5", 300 lb. capacity.

Type	Model No.	Weight(Lbs.)	Weight(kg.)
Swivel (Set of 4)	CA5S4	13	5.9
Swivel w/Brake (Set of 4)	CA5BP4	10	4.5
Swivel, 2 w/Brake (Set of 4)	CA5SB	10	4.5
Swivel, 2 w/Brake, 2 Rigid (Set of 4)	CA5RSB*	10	4.5
Stainless Steel, Swivel, 2 w/Brake (Set of 4)	CA5SBS	15	6.8

Description: Pneumatic Wheel, 2.5" x 8", 300 lb. capacity.

Type	Model No.	Weight(Lbs.)	Weight(kg.)
2 Swivel, 2 Rigid (Set of 4)	CA85RN*	14	6.4

*Tie Bar required